

■ 布入ゴムVパッキン寸法表 (JIS B 2403)

呼び番号		呼び寸法			高さ B		R				
		内径 d	外径 D	幅 W	基準寸法	許容差	最小				
F	6.3	6.3	16.3	5	3	+ 0.5 - 0.2	0.5				
F	7.1	7.1	17.1								
F	8	8	18								
F	9	9	19								
F	10	10	20								
F	11.2	11.2	21.2								
F	12.5	12.5	22.5								
F	14	14	24								
F	16	16	26								
F	15	15	28	6.5	3	+ 0.5 - 0.2	0.75				
F	18	18	31								
F	18.5	18.5	31.5								
F	20	20	33								
F	22.4	22.4	35.4								
F	25	25	38								
F	27	27	40								
F	28	28	41								
F	31.5	31.5	44.5								
F	32	32	45								
F	34	34	50	8	4	+ 0.5 - 0.2	1				
F	35.5	35.5	51.5								
F	40	40	56								
F	45	45	61								
F	47	47	63								
F	50	50	66								
F	53	53	69								
F	55	55	71								
F	56	56	72								
F	60	60	76								
F	63	63	79								
F	64	64	80								
F	67	67	87	10	5	+ 0.5 - 0.2	2				
F	70	70	90								
F	71	71	91								
F	75	75	95								
F	80	80	100								
F	85	85	105								
F	90	90	110								
F	92	92	112								
F	95	95	115								
F	100	100	120	10	5	+ 0.5 - 0.2	2				
F	105	105	125								
F	106	106	126								
F	112	112	132								
F	118	118	138								
F	120	120	140								
F	125	125	150					12.5	6	+ 0.5 - 0.2	2
F	132	132	157								
F	135	135	160								
F	140	140	165								
F	145	145	170								
F	150	150	175								
F	155	155	180								
F	160	160	185								
F	165	165	190								
F	170	170	195	12.5	6	+ 0.5 - 0.2	2				
F	175	175	200								
F	180	180	205								
F	190	190	215								
F	199	199	224								
F	200	200	225								
F	212	212	237								
F	224	224	249								
F	225	225	250								
F	236	236	261								
F	250	250	275								
F	265	265	297	16	7	+ 0.8 - 0.3	3				
F	280	280	312								
F	300	300	332								
F	315	315	347								
F	335	335	367								
F	355	355	387								
F	375	375	407								
F	400	400	432								
F	425	425	457								
F	450	450	482	20	8	+ 1.2 - 0.4	4				
F	475	475	507								
F	500	500	532								
F	530	530	570								
F	560	560	600								
F	600	600	640								
F	630	630	670								
F	670	670	710								
F	710	710	750								
F	750	750	790								
F	800	800	840								
F	850	850	890								
F	900	900	940								
F	950	950	990								
F	1000	1000	1040								



■ゴムVパッキン寸法表 (JIS B 2403)

単位mm

呼び番号	呼び寸法			高さ B		R				
	内径 d	外径 D	幅 W	基準寸法	許容差	最小				
H 6.3	6.3	16.3	5	2.5	± 0.3	0.5				
H 7.1	7.1	17.1								
H 8	8	18								
H 9	9	19								
H 10	10	20								
H 11.2	11.2	21.2								
H 12.5	12.5	22.5								
H 14	14	24								
H 16	16	26								
H 15	15	28	6.5	3	± 0.3	0.75				
H 18	18	31								
H 18.5	18.5	31.5								
H 20	20	33								
H 22.4	22.4	35.4								
H 25	25	38								
H 27	27	40								
H 28	28	41								
H 31.5	31.5	44.5								
H 32	32	45								
H 34	34	50	8	3.5	± 0.5	1				
H 35.5	35.5	51.5								
H 40	40	56								
H 45	45	61								
H 47	47	63								
H 50	50	66								
H 53	53	69								
H 55	55	71								
H 56	56	72								
H 60	60	76								
H 63	63	79								
H 64	64	80								
H 67	67	87	10	4	± 0.3	2				
H 70	70	90								
H 71	71	91								
H 75	75	95								
H 80	80	100								
H 85	85	105	10	4	± 0.3	2				
H 90	90	110								
H 92	92	112								
H 95	95	115								
H 100	100	120								
H 105	105	125								
H 106	106	126								
H 112	112	132								
H 118	118	138								
H 120	120	140								
H 125	125	150					12.5	5	± 0.3	2
H 132	132	157								
H 135	135	160								
H 140	140	165								
H 145	145	170								
H 150	150	175								
H 155	155	180								
H 160	160	185								
H 165	165	190								
H 170	170	195								
H 175	175	200								
H 180	180	205								
H 190	190	215								
H 199	199	224								
H 200	200	225								
H 212	212	237								
H 224	224	249								
H 225	225	250								
H 236	236	261								
H 250	250	275								
H 265	265	297	16	6	± 0.4	3				
H 280	280	312								
H 300	300	332								